

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 09/11/2015 Supersedes: 07/14/2015 Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

: EasiSolv 701 Screen Wash & Stain Remover

Product name Product form

· Mixture

Product form

. Mixidle

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

: To remove ink and ink stains

1.3. Details of the supplier of the safety data sheet

Easiway Systems, Inc. 540 S. River Street Delano, MN 55328 Phone: 1-763-972-6306 Web: www.easiway.com E-Mail: sales@easiway.com

1.4. Emergency telephone number

CHEMTREC: USA/Canada 1-800-424-9300 // Argentina +(54)-1159839431 // Australia +(61)-290372994 // Austria +(43)-13649237 // Bahrain +(973)-16199372 // Belgium +(32)-28083237 // Brazil +(55)-2319581449 // Bulgaria +(359)-32570104 // Chile +(56)-225814934 // China 4001-204937 // Colombia 01800-710-2151 // Croatia +(385)-17776920 // Czech Republic +(420)-228880039 // Denmark +(45)-69918573 // Finland +(358)-942419014 // France +(33)-975181407 // Germany 0800-181-7059 // Hong Kong 800-968-793 // Hungary +(36)-18088425 // India 000-800-100-7141 // Indonesia 001-803-017-9114 // Ireland +(353)-19014670 // Israel +(972)-37630639 // Italy 800-789-767 // Japan +(81)-845209637 // Luxembourg +(352)-20202416 // Malaysia 1-800-815-308 // Mexico 01-800-681-9531 // Netherlands +(31)-858880596 // New Zealand +(64)-98010034 // Norway +(47)-21930678 // Peru +(51)-17071295 // Philippines 1-800-1-116-1020 // Poland +(48)-223988029 // Portugal +(351)-308801773 // Russia 8-800-100-6346 // Saudi Arabia +(966)-8111095861 // Singapore 800-101-2201 // Slovakia +(421)-233057972 // Slovania +(386)-18888016 // South Africa 0-800-983-611 // South Korea 00-308-13-2549 // Spain 900-868538 // Sweden +(46)-852503403 // Switzerland +(41)-435082011 // Taiwan 00801-14-8954 // Thailand 001-800-13-203-9987 // Turkey +(90)-212-7055340 // Ukraine +(380)-947101374 // UK +(44)-870-8200418

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

 Flam. Liq. 4
 H227

 Skin Irrit. 2
 H315

 Eye Dam. 1
 H318

 Asp. Tox. 1
 H304

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US):



Signal word (GHS-US): Danger

- Hazard statements (GHS-US): H227 Combustible liquid; H304 May be fatal if swallowed and enters airways; H315 May cause skin irritation; H318 May cause serious eye damage
- Precautionary statements (GHS-US): P210 Keep away from open flames, heat. No smoking; P264 Wash hands, forearms and face thoroughly after handling; P280 Wear eye protection, face protection, protective clothing, protective gloves; P301+P310 IF SWALLOWED: Immediately call a doctor, a POISON CENTER; P302+P352 If on skin: Wash with plenty of water; P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing; P310 Immediately call a doctor, a POISON CENTER; P321 Specific treatment (see first aid instructions on this label); P331 Do NOT induce vomiting; P332+P313 If skin irritation occurs: Get medical advice/attention; P362+P364 Take off contaminated clothing and wash it before reuse; P370+P378 In case of fire: Use foam, carbon dioxide (CO2), dry extinguishing powder, sand to extinguish; P403+P235 Store in a well-ventilated place. Keep cool; P501 Dispose of contents/container to a facility that complies with all local, state, regional, federal, national, and international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Safety Data Sheet

3.2.

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%
Aliphatic dibasic esters	Proprietary	30 - 60
Propanol, 1(or 2)-(2-methoxymethylethoxy)-, acetate	(CAS No) 88917-22-0	15 - 40
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	7 - 13
Poly(oxy-1,2-ethanediyl), .alpha(4-nonylphenyl)omegahydroxy-, branched	(CAS No) 127087-87-0	1 - 10
Glycol ethers	Proprietary	1 - 5
2-Butoxyethanol	(CAS No) 111-76-2	0.1 - 1

SECTION 4: First aid measures

4.1. Description of first aid measur	es
First-aid measures general	 If concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
First-aid measures after inhalation	: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
First-aid measures after skin contact	: IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water. If irritation develops or persists, get medical attention.
First-aid measures after eye contact	: IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.
First-aid measures after ingestion	: IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.
4.2. Most important symptoms and	l effects, both acute and delayed
Symptoms/injuries	: May be fatal if swallowed and enters airways. May cause skin irritation. May cause serious eye damage.
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: May cause skin irritation.
Symptoms/injuries after eye contact	: May cause serious eye damage.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

SECTION 5: Firefighting measures			
5.1. Extinguishing media			
Suitable extinguishing media	: Foam. Carbon dioxide. Dry powder. Water spray. Sand.		
Unsuitable extinguishing media	: None known.		
5.2. Special hazards arising from the substance or mixture			
Fire hazard	: Combustible liquid.		
Explosion hazard	: Product is not explosive.		
Reactivity	: No dangerous reactions known under normal conditions of use.		
5.3. Advice for firefighters			
Precautionary measures fire	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.		
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.		
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.		
SECTION 6: Accidental release measures			
6.1. Personal precautions, protective equipment and emergency procedures			
General measures	: Ventilate area. Keep upwind. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).		
6.1.1. For non-emergency personne			

6.1.1. For non-emergency personner		
Protective equipment	: Wear Protective equipment as described in Section 8.	
Emergency procedures	: Evacuate unnecessary personnel.	
6.1.2. For emergency responders		
Protective equipment	: Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.	

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.2. Environmental precautions

Prevent entry to untreated waste streams and public waters. Notify authorities if liquid enters untreated waste streams and or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up		
For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.	
Methods for cleaning up	Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Sweep or shovel spills into appropriate container for disposal. This material and its container must be disposed of in a safe way, and as per local legislation.	
6.4. Reference to other section	ions	
See Sections 8 and 13.		
SECTION 7: Handling and	storage	

7.1.	Precautions for safe handling	
Precaut	ions for safe handling	Do not handle until all safety precautions have been read and understood. Keep away from sources of ignition - No smoking. Provide appropriate exhaust ventilation at places of dust forming. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep the container tightly closed. Store in a dry, cool and well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Propanol, 1(or 2)-(2-methoxymethylethoxy)-, acetate (88917-22-0)			
Remark (ACGIH)	OELs not established		
Remark (OSHA)	OELs not established		
Petroleum distillates, hydrotreated light (64742-47-8)			
Remark (ACGIH)	OELs not established		
Remark (OSHA)	OELs not established		
2-Butoxyethanol (111-76-2)			
ACGIH TWA (ppm)	20		
Remark (ACGIH)	eye and upper respiratory tract irritation		
OSHA PEL (TWA) (mg/m³)	240		
OSHA PEL (TWA) (ppm)	50		
Poly(oxy-1,2-ethanediyl), .alpha(4-nonylphenyl)omegahydroxy-, branched (127087-87-0)			
Remark (ACGIH)	OELs not established		
Remark (OSHA)	OELs not established		

8.2. Exposure controls

Personal protective equipment

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.



: Wear safety glasses with side shields (or goggles). Use a face shield, if necessary.

 Wear impervious gloves to prevent contact with the skin. Wear protective gear as needed – apron, suit, boots.

- : NIOSH-approved (or equivalent) respirators may be necessary if airborne concentrations are expected to exceed exposure limits.
- Other Protective Equipment : Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties Physical state : Liquid

Physical state	. Liqu
Color	: Clea

: Clear amber.

Eye protection

Skin and body protection

Respiratory protection

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor	: Mild ether.
Odor Threshold	: No data available
рН	: Neutral
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 196 °C 385 °F
Flash point	: 91 °C 196 °F (Setaflash)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 0.08 mm Hg @ 20 °C / 68 °F
Relative vapour density at 20 °C	: Heavier than air
Relative density	: 1.01 @ 20 °C / 68 °F
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: < 10 cPs
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
9.2. Other information	

No additional information available

SECTION 10: Stability and reactivity			
10.1.	Reactivity	-	No dangerous reactions known under normal conditions of use
10.2.	Chemical stability	-	Stable under recommended handling and storage conditions (see section 7).
10.3.	Possibility of hazardous reactions	:	None known.
10.4.	Conditions to avoid	-	None known.
10.5.	Incompatible materials	-	Strong acids. Strong oxidizing agents. Strong alkalis
10.6.	Hazardous decomposition products	s :	Carbon oxides (CO, CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects			
Acute toxicity	: Not classified		
EasiSolv 701 Screen Wash & Stain Remover			
LD50 oral rat	> 3000 mg/kg		
LD50 dermal rabbit	> 2000 mg/kg		
LC50 inhalation rat (mg/l)	> 11 mg/l/4h		
Petroleum distillates, hydrotreated light (64742-47-8)			
LD50 oral rat	> 5000 mg/kg		
LD50 dermal rabbit	> 2000 mg/kg		
LC50 inhalation rat (mg/l)	> 5.2 mg/l/4h		
2-Butoxyethanol (111-76-2)			
LD50 oral rat	470 mg/kg		
ATE CLP (oral)	500.000 mg/kg bodyweight		
ATE CLP (dermal)	1100.000 mg/kg bodyweight		
ATE CLP (gases)	4500.000 ppmv/4h		
ATE CLP (vapours)	11.000 mg/l/4h		
ATE CLP (dust,mist)	1.500 mg/l/4h		
Poly(oxy-1,2-ethanediyl), .alpha(4-nonylphenyl)omegahydroxy-, branched (127087-87-0)			
LD50 oral rat	1310 mg/kg		

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation	: May cause skin irritation. pH: Neutral
Serious eye damage/irritation	: May cause serious eye damage. pH: Neutral
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: May cause skin irritation.
Symptoms/injuries after eye contact	: May cause serious eye damage.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

Ecology - general	: No information available.
SECTION 13: Disposal consideration	S
13.1. Waste treatment methods	
Waste treatment methods	: Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.
SECTION 14: Transport information	
In accordance with DOT	
Transport document description	: NA1993 Combustible liquid, n.o.s. (Contains: Dipropylene glycol methyl ether acetate), 3, III
DOT NA no.	: NA1993
Proper Shipping Name (DOT)	: Combustible liquid, n.o.s.
	Contains: Dipropylene glycol methyl ether acetate
Department of Transportation (DOT) Hazard Classes	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: III - Minor Danger
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Other information	: No supplementary information available.

SECTION 15: Regulatory information

EasiSolv 701 Screen Wash & Stain Remov	rer
	sted in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory gistered in the EINECS inventory or in the ELINCS list
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard
2-Butoxyethanol (111-76-2)	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	&
Section 313	Listed on US SARA Section 313

No additional information availableNo additional information available

Transport by Sea

Air transport

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylene oxide (75-21-8)		
Section 302 (EHS) TPQ	1000	lb
Section 304 EHS RQ	10	lb
CERCLA RQ	10	lb
Section 313	Listed on US SARA Section 313	

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

Ethylene oxide (75-21-8)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	Yes	Yes	2 µg/day

SECTION 16: Other info	ormation		
Indication of changes	: Revision 3.0: Sections 2,4,6,8,11,12.		
Revision date	: 09/11/2015		
Other information	: Author: KRK.		
NFPA health hazard:	2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.		
NFPA fire hazard:	2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.		
NFPA reactivity:	 Normally stable, even under fire exposure conditions, and are not reactive with water. 		
NFPA specific hazard:		\sim	
HMIS III Health:	2 - Temporary or minor injury may occur.	Health	2
HMIS III Flammability:	2 - Materials which must be moderately heated or exposed to high ambient	Flammability	2
	temperatures before ignition will occur. Includes liquids having a flash point at or above 100 °F (38 °C) but below 200 °F (93 °C).	Reactivity	0
HMIS III Physical:	0 - Materials that are normally stable, even under fire conditions, and will	Personal Protection	J
	not react with water, polymerize, decompose, condense, or self-react. Non- explosives.		
HMIS III Personal Protection:	Gloves. Wear chemical goggles and face shield in combination. Wear chemically impervious apron over lab coat and full coverage clothing. Insufficient ventilation: wear respiratory protection.		

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product