

Material Safety Data Sheet-Van Son All Purpose Fountain Solution

Date: 1-1-2012

	H	M	I	S	
Minimal Slight Moderate	Hazard 0 1 2	Ratings Serious Severe	3 4	Health Flammability Reactivity	2 2 0

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

DISTRIBUTOR: Van Son Holland Ink Corporation of America MANUFACTURER:

888 Vets Hwy. Hauppauge, NY 11788 Tower Products, Inc., 2703 Freemansburg Ave.,

Emergency Telephone: 631-715-7000 Product Class: Fountain Solution

Chemtrec 24 Hour Emergency No-800-424-9300

Easton, PA 18045

Trade Name: Van Son All Purpose Fountain Solution

Manufacturer's Code ID: V2020

2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CASNo.	WT%	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Solvent EB	111-76-2	9.07	240mg/M3	240mg/M3	No
(Syn.: 2-Butoxyethanol)					
Isopropyl Alcohol	67-63-0	5-15	980mg/M3	980mg/M3	No
(Syn.: IPA, Isopropanol)					

3. HAZARDS IDENTIFICATION

OSHA Hazard Communication 29 CFR 1910.1200 Isopropyl Alcohol, 2-Butoxyethanol				
EFFECTS OF OVEREXPOSURE				
Eye Contact				
Skin Contact				
attention if necessary.				
Inhalation				
Ingestion				
Make physician aware of product ingredients				
Medical Conditions aggravated by normal exposure: Persons with dermatitis should avoid skin contact.				
Target Organs:				
Primary Routes of entry Eyes, inhalation, dermal.				
Systemic and other effects				
blood abnormalities, and kidney and lung damage in laboratory animals; may cause maternal toxicity. Chronic overexposure to IPA has				
caused liver abnormalities, and kidney and brain damage in laboratory animals.				
EMERGENCY FIRST AID PROCEDURES				
Eye Contact				
medical attention.				
Skin Contact:				
skin areas with scap and water. Seek medical attention if inritation persists				
Ingestion				
5. FIRE FIGHTING MEASURES				
Flash Point				
Explosion LimitsLEL: N/A UEL: N/A				
Extinguishing MediaW ater				
Unusual Fire and Explosion Hazards. Keep work areas free of hot metal surfaces and other sources of ignition.				

6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released: Stop and/or contain discharge if it may be done safely. Keep all sources of ignition away and use non-sparking tools for clean up. Ventilate area of spill and cover with inert material to reduce furnes if necessary. Keep out of drains, sewers or waterways. Notify local health and pollution control agencies, and call spill response teams if large spill.

clothing. Use water spray to cool nearby containers and structures exposed to

Special Fire Fighting Procedures Fire fighters should wear self-contained breathing apparatus and full protective

W aste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling: Keep product containers cool, dry and away from source of ignition. Use with adequate ventilation. Keep containers closed when not in use. Other Precautions: Avoid inhalation of vapors. Avoid personal contact with product. Empty containers may contain product residue and/or vapors.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: Local and mechanical exhaust recommended. Avoid open electrical sources near product vapor areas. Protective Gloves: Impermeable gloves recommended to prevent skin irritation and absorption.

Respiratory Protection: None normally necessary when this product is used in its intended manner.

Eye Protection: Safety glasses are recommended to safeguard against potential eye contat, initation and injury. Other Protection: The availability of eye washes, safety shoes, aprons and safety showers is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 1.5 lbs./gallon 200 Gra Boiling Point: 180 degrees F (IBP Isopropyl Alcohol) Freezin

Vapor Density vs. Air: Heavier

Density: 9.00 lbs./gallon ASTM D1475

Type of Odor: Alcohol

Appearance: Pink Liquid

Evaporation Rate vs. Butyl Acetate: slower

200 Grams/liter Method 24 Freezing Point °F: N/A Vapor Pressure: N/A Specific Gravity: 0.98 Odor Threshold: Mild

pH: 4.0

Coefficient of Water/oil Distribution: N/A

10. STABILITY AND REACTIVITY

Product Stability: Stable

Materials to Avoid: Strong oxidizing agents, acids and bases. Avoid storage above 90 F. Keep containers closed when not

ın use.

Hazardous Decomposition Products: Thermal decomposition in the presence of air may yield carbon monoxide and/or carbon dioxide.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogen	
	Program (NTP), or The International Agency for Research on Cancer (IARC)
Mutagen	No
Teratogen	No
Reproductive Toxicity	No

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental prob-

13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

14. TRANSPORT INFORMATION - DOT (HM 181) : Not required Shipping Labels: None required

15. REGULATORY INFORMATION

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.