

MATERIAL SAFETY DATA SHEET

Bulldog Adhesion Promoter



HEALTH		3
FLAMMABILITY		3
PHYSICAL HAZ.		0
PPE		X



Printed: 07/24/2009
 Revision: 07/23/2009
 Supersedes Revision: 10/09/2008
 Date Created: 08/21/2007

1. Product and Company Identification

Product Code: 5000.2WHMIS
Product Name: Bulldog Adhesion Promoter
Reference #: 5000.2
Manufacturer Information
Company Name: W. M. Barr
 2105 Channel Avenue
 Memphis, TN 38113
Phone Number: (901)775-0100
Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346
Information: W.M. Barr Customer Service (800)398-3892
Web site address: www.wmbarr.com
Preparer Name: W.M. Barr EHS Dept (901)775-0100
Synonyms
 QTPO123, GTPO123, PTPO123

2. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Concentration	OSHA TWA	ACGIH TWA	Other Limits
1. Toluene {Benzene, Methyl-; Toluol}	108-88-3	15.0 -40.0 %	200 ppm	50 ppm	No data.
2. Styrene {Phenylethylene; Vinyl benzine; Styrol}	100-42-5	3.0 -7.0 %	100 ppm	20 ppm	No data.
3. m-Xylene {Benzene, m-Dimethyl-}	108-38-3	5.0 -10.0 %	No data.	100 ppm	No data.
4. o-Xylene {Benzene, o-Dimethyl-}	95-47-6	1.0 -5.0 %	100 ppm	100 ppm	No data.
5. p-Xylene {Benzene, p-Dimethyl-}	106-42-3	1.0 -5.0 %	No data.	100 ppm	No data.
6. Ethylbenzene {Ethylbenzol; Phenylethane}	100-41-4	1.0 -10.0 %	100 ppm	100 ppm	No data.
7. Divinyl benzene (Benzene, Diethenyl-)	1321-74-0	1.0 -5.0 %	No data.	10 ppm	No data.
8. Methyl ethyl ketone {MEK; 2-Butanone}	78-93-3	10.0 -30.0 %	200 ppm	200 ppm	No data.
9. Butyl acetate {Acetic acid, Butyl ester}	123-86-4	10.0 -30.0 %	150 ppm	150 ppm	No data.
10. Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	111-76-2	1.0 -5.0 %	50 ppm	20 ppm	No data.
11. Ethyl methacrylate	97-63-2	1.0 -5.0 %	No data.	No data.	No data.

Hazardous Components (Chemical Name)	CAS #	OSHA STEL	OSHA CEIL	ACGIH STEL	ACGIH CEIL
1. Toluene {Benzene, Methyl-; Toluol}	108-88-3	500 ppm/(10min)	300 ppm	No data.	No data.
2. Styrene {Phenylethylene; Vinyl benzine; Styrol}	100-42-5	600 ppm/(5min/3hr)	200 ppm	40 ppm	No data.
3. m-Xylene {Benzene, m-Dimethyl-}	108-38-3	No data.	No data.	150 ppm	No data.
4. o-Xylene {Benzene, o-Dimethyl-}	95-47-6	No data.	No data.	150 ppm	No data.
5. p-Xylene {Benzene, p-Dimethyl-}	106-42-3	No data.	No data.	150 ppm	No data.
6. Ethylbenzene {Ethylbenzol; Phenylethane}	100-41-4	No data.	No data.	125 ppm	No data.
7. Divinyl benzene (Benzene, Diethenyl-)	1321-74-0	No data.	No data.	No data.	No data.
8. Methyl ethyl ketone {MEK; 2-Butanone}	78-93-3	No data.	No data.	300 ppm	No data.
9. Butyl acetate {Acetic acid, Butyl ester}	123-86-4	No data.	No data.	200 ppm	No data.
10. Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	111-76-2	No data.	No data.	No data.	No data.
11. Ethyl methacrylate	97-63-2	No data.	No data.	No data.	No data.

3. Hazards Identification

Emergency Overview

Danger! Flammable. Harmful or fatal if swallowed. Vapor Harmful. Skin and Eye Irritant.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic)

INHALATION ACUTE EXPOSURE EFFECTS:

Vapor Harmful. May cause dizziness, headache, irritation of the upper respiratory tract and lungs, irritation and injury to mucous membranes, watering of the eyes, weakness, drowsiness, nausea, loss of coordination, numbness in fingers, arms and legs, depression of the central nervous system, pulmonary edema, shortness of breath, loss of appetite, fatigue, stupor, anesthesia, narcosis, vomiting, lightheadedness, liver and kidney injury, insensibility and other central nervous system effects, blood disorders, nose tumors, brain damage, giddiness, olfactory changes, confusion, hearing impairment, slurred speech, coughing, hallucinations, irregular heartbeat, unconsciousness, coma, and death. Intentional misuse of this product by deliberately concentrating and inhaling vapors can be harmful or fatal.

SKIN CONTACT ACUTE EXPOSURE EFFECTS:

This product is a skin irritant. Product may be absorbed through the skin. May cause irritation, drying and cracking of the skin, defatting of the skin, dermatitis, itching, redness, swelling, tissue damage, inflammation, numbness in fingers and arms, discomfort or pain, erythema. May be absorbed readily to produce symptoms similar to those listed under ingestion.

EYE CONTACT ACUTE EXPOSURE EFFECTS:

This material is an eye irritant. May cause redness, tearing, corneal clouding, discomfort or pain with excessive blinking and tear production, excess redness and possible slight swelling of the conjunctiva, stinging, conjunctivitis, visual intolerance to light. If not promptly removed, will injure eye tissue, which may result in permanent damage.

INGESTION ACUTE EXPOSURE EFFECTS:

Harmful or fatal if swallowed. May cause dizziness, headache, drowsiness, nausea, weakness, loss of coordination, irritation to mouth, throat and stomach, vomiting, gastrointestinal irritation, diarrhea, loss of appetite, pain and discomfort, cough and hoarseness, salivation, changes in white blood cells, burning sensation in mouth and stomach, unconsciousness and coma. Ingestion of significant quantities may result in red blood cell hemolysis. Liquid aspirated into lungs can cause chemical pneumonitis, which can be fatal.

CHRONIC EXPOSURE EFFECTS:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Prolonged skin contact may result in absorption of a harmful amount of this material. Prolonged or repeated contact may cause dermatitis. May cause dizziness, headaches, weakness, eye irritation, drying and cracking of the skin, dermatitis, fatigue, nausea, numbness in the hands and feet, permanent central nervous system changes, some loss of memory, liver and kidney damage, blood disorders, thyroid effects, enlarged liver, and irritation to the respiratory tract. Prolonged or repeated contact may cause skin irritation, even a burn. Prolonged exposure may cause slight swelling of the conjunctiva, blurring of vision may occur. Prolonged skin contact may cause mild to moderate redness and swelling.

Signs and Symptoms Of Exposure

Primary Routes of Exposure: Inhalation, Skin Contact.

Medical Conditions Generally Aggravated By Exposure

Diseases of the skin, liver, kidneys, and cardiovascular system.

4. First Aid Measures

Emergency and First Aid Procedures

INHALATION:

If user experiences breathing difficulty, move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

SKIN CONTACT:

Wash with soap and water. Get medical attention if irritation develops or persists.

EYE CONTACT:

Immediately flush eyes with water for at least 15 minutes. Remove contact lenses if worn. Seek medical attention.

INGESTION:

If swallowed, do NOT induce vomiting. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.

5. Fire Fighting Measures

Flammability Classification:

IB

Flash Pt:

39.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)

Explosive Limits:

LEL: No data.

UEL: No data.

Fire Fighting Instructions

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

Flammable Properties and Hazards

Danger! Flammable! Keep away from heat, sparks, flame, and all other sources of ignition. Do not smoke.

Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Beware of static electricity that may be generated by synthetic clothing and other sources. Vapors can travel to a source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide and carbon dioxide. Irritating or toxic vapors and gases.

Extinguishing Media

Use carbon dioxide, dry powder, or foam.

Unsuitable Extinguishing Media

No data available.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Wear appropriate personal protective equipment.

Small Spills: take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large Spills: dike far ahead of spill for later disposal.

7. Handling and Storage

Precautions To Be Taken in Handling

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Precautions To Be Taken in Storing

Store in a cool dry place. Avoid extreme high or low temperatures.

8. Exposure Controls/Personal Protection

Respiratory Equipment (Specify Type)

A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

If the work area is not properly ventilated to keep airborne levels below their exposure limits, you must use a properly fitted and maintained NIOSH approved respirator for organic vapors. A dust mask does not provide protection against vapors.

Eye Protection

Safety glasses, chemical goggles, or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

Protective Gloves

Wear impermeable gloves. Gloves contaminated with product should be discarded.

Other Protective Clothing

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.

Engineering Controls (Ventilation etc.)

Use only with adequate ventilation to prevent the buildup of vapors. Do not use in areas where vapors can accumulate and concentrate. Whenever possible, use outdoors in an open air area. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area away from the individual. If strong odor is noticed or you experience slight dizziness, headache, nausea, or other signs of inhalation exposure, STOP. The ventilation is inadequate. Leave the area immediately.

For OSHA controlled workplaces, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Work/Hygienic/Maintenance Practices

A source of clean water should be available in the work area for flushing of the eyes and skin. Wash hands thoroughly after use. Do not eat, drink, or smoke in the work area. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

9. Physical and Chemical Properties

Physical States:	[] Gas	[X] Liquid	[] Solid
Melting Point:	No data.		
Boiling Point:	No data.		
Autoignition Pt:	No data.		
Flash Pt:	39.00 F	Method Used:	Setaflash Closed Cup (Rapid Setaflash)
Explosive Limits:	LEL: No data.	UEL:	No data.
Specific Gravity (Water = 1):	0.9 - 0.915		
Bulk density:	7.54 LB/GL		

MATERIAL SAFETY DATA SHEET

Bulldog Adhesion Promoter

Page: 5

Printed: 07/24/2009

Revision: 07/23/2009

Supersedes Revision: 10/09/2008

Vapor Pressure (vs. Air or mm Hg):	<=26 MM HG at 20.0 C
Vapor Density (vs. Air = 1):	> 1
Evaporation Rate (vs Butyl Acetate=1):	~ 1
Solubility in Water:	No data.
Percent Volatile:	82.75 %
VOC / Volume:	<= 748.0000 G/L
Heat Value:	No data.
Particle Size:	No data.
Corrosion Rate:	No data.
pH:	No data.

Appearance and Odor

Hazy, light yellow

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid - Instability

No data available.

Incompatibility - Materials To Avoid

Incompatible with strong oxidizing agents, strong caustics, acids, strong bases, hydrogen peroxide, nitric acid, nitrates, sulfuric acid, amines, chemically active metals, salts, aldehydes, ammonia, and halogens.

Hazardous Decomposition Or Byproducts

Thermal decomposition may produce carbon monoxide, carbon dioxide, acrylic monomers, acrid smoke and fumes.

Hazardous Polymerization: Will occur [] Will not occur [X]

Conditions To Avoid - Hazardous Polymerization

No data available.

11. Toxicological Information

Toluene:

LD50 Rat oral 2.6 to 7.5 g/kg

LD50 Rabbit dermal 14.1 ml/kg

LD50 Rat (female) ip 1.64 g/kg

LD50 MOUSE IP 1.15 G/KG

LD50 Rat oral 5000 mg/kg

LD50 Rat ip 1332 mg/kg

LD50 Rat iv 1960 mg/kg

LC50 Mouse ihl 400 ppm/24 hr

LD50 Mouse ip 59 mg/kg

LD50 Mouse sc 2250 mg/kg

LD50 Mouse ip 640 mg/kg

LD50 Rabbit skin 12,124 mg/kg

LC50 for toluene in mice is 5320 ppm/8 hr /via inhalation/ ...

As the duration of toluene inhalation exposure increased, the LC50 in rats decreased from 26,700 ppm for 1 hr, to 12,200 ppm for 2-2.5 hr, to 8000 ppm for 4 hr.

Styrene:

LD50 Mouse ip 660 + or - 44.3 mg/kg

LD50 Mouse iv 90 + or - 5.2 mg/kg

LC50 Mouse inhalation 4940 ppm/2 hr

LC50 Rat inhalation 2770 ppm/4 hr

MATERIAL SAFETY DATA SHEET
Bulldog Adhesion Promoter

Page: 6

Printed: 07/24/2009

Revision: 07/23/2009

Supercedes Revision: 10/09/2008

LD50 Rat oral, male and female 5000 mg/kg
LD50 Rat oral 1 g/kg
LD50 Rat ip 898 mg/kg
LC50 Rat inhalation 24 g/cu m/4 hr
LD50 Mouse oral 316 mg/kg

Xylenes:

LD50 Rat oral 4.3 g/kg
LD50 Rat oral 10 mL/kg /Xylene/
LD50 Mouse oral 1590 mg/kg /Xylene/
LC50 Rat inhalation 6,350 ppm/4 hr
LCLo Rat inhalation 8,000 ppm/4 hr
LC50 Rat inhalation 6,350 ppm/4 hr
LC50 Mouse inhalation 3,907 ppm/6 hr
LD50 Rat oral 4.3 g/kg and 10 ml/kg /Xylene/
LD50 Mouse oral 1590 mg/kg /Xylene/
LC50 Rat oral 29,000 mg/cu m (6670 ppm) /Xylene/
LD50 Rat oral range from 3523 mg/kg to 8600 mg/kg. /Mixed Xylenes/
LD50 Mouse (B6C3F1) oral 5251 mg/kg (female) and 5627 mg/kg (male). /Mixed Xylenes/
LD50 Rabbit dermal > 5 ml/kg (43 g/kg). /Mixed Xylenes/

Ethylbenzene:

LD50 Rat oral 5.46 g/kg.
LD50 Rat oral 3500 mg/kg
LD50 Mouse ip 2272 mg/kg
LD50 Rabbit skin 17,800 mg/kg

Divinyl Benzene:

LD50 Rat (male) oral 4640 mg/kg
LD50 Rat (female) oral 4100 mg/kg

Methyl Ethyl Ketone:

LC50 Rat inhalation >5000 ppm/6 hr
LD50 Rat oral 3400 mg/kg bw
LD50 Rat oral 2900 (95% C.I. 2300-3500) mg/kg /From table/
LD50 Rat (female) oral 5520 (95% C.I. 4500-6800) mg/kg /From table/
LD50 Mouse (male) oral 3140 + or - 670 mg/kg /From table/
LC50 (45 min) Mouse (male) inhalation 205,000 + or - 32,500 mg/cu m (69,500 + or - 11,000 ppm) /From table/
LC50 (4 hr) Rat (male) inhalation 34,500 mg/cu m (11,700 ppm) /From table/
LD50 (24 hr) Mouse (male) ip 1660 + or - 740 mg/kg /From table/
LD50 (24 hr) Rat (female) ip 15540 (95% CI 12290-19660) mg/kg /From table/
LD50 (14 day) Rat (female) ip 6070 (95% C.I. 4860-7480) g/kg /From table/
LD50 (14 days) Rabbit (male) dermal >8000 mg/kg /From table; 24-hr occluded exposure duration/

Butyl Acetate:

Irritant dose guinea pig ocular 3300 ppm/13 hr
LD50 Rat oral 14.0 g/kg /From table/
LD50 Rat oral 14.13 g/kg
LC50 Wistar rats inhalation 160 ppm/4hr

Ethylene Glycol Monobutyl Ether Acetate:

MATERIAL SAFETY DATA SHEET

Bulldog Adhesion Promoter

Page: 7

Printed: 07/24/2009

Revision: 07/23/2009

Supersedes Revision: 10/09/2008

LD50 RAT FEMALE ORAL 2400 MG/KG

LD50 RAT MALE ORAL 3000 MG/KG

Ethyl Methacrylate:

LD50 Rabbit dermal >9.1 g/kg

LD50 Rat oral 14,800 mg/kg

LC50 Rat ihl 8300 ppm/4 hr

LD50 Rat ip 1223 mg/kg

LD50 Mouse oral 7836 mg/kg

LD50 Mouse ip 1369 mg/kg

Carcinogenicity/Other Information

-Ethyl Benzene (CAS 100-41-4) is on the IARC list as a Group 2B: Possibly Carcinogenic to Humans.

-Styrene (CAS 100-42-5) is on the IARC list as a Group 2B: Possibly Carcinogenic to Humans.

-Toluene (CAS 108-88-3) is on the IARC list as a Group 3: Not Classifiable as to Carcinogenicity in Humans.

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1. Toluene {Benzene, Methyl-; Toluol}	108-88-3	No	3	A4	No
2. Styrene {Phenylethylene; Vinyl benzene; Styrol}	100-42-5	No	2B	A4	No
3. m-Xylene {Benzene, m-Dimethyl-}	108-38-3	n.a.	n.a.	A4	n.a.
4. o-Xylene {Benzene, o-Dimethyl-}	95-47-6	n.a.	n.a.	A4	n.a.
5. p-Xylene {Benzene, p-Dimethyl-}	106-42-3	n.a.	n.a.	A4	n.a.
6. Ethylbenzene {Ethylbenzol; Phenylethane}	100-41-4	No	2B	A3	No
7. Divinyl benzene (Benzene, Diethenyl-)	1321-74-0	n.a.	n.a.	n.a.	n.a.
8. Methyl ethyl ketone {MEK; 2-Butanone}	78-93-3	n.a.	n.a.	n.a.	n.a.
9. Butyl acetate {Acetic acid, Butyl ester}	123-86-4	n.a.	n.a.	n.a.	n.a.
10. Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	111-76-2	Possible	2B	A3	No
11. Ethyl methacrylate	97-63-2	n.a.	n.a.	n.a.	n.a.

12. Ecological Information

No data available.

13. Disposal Considerations

Waste Disposal Method

Dispose of in accordance with all applicable local, state, and federal regulations.

14. Transport Information

LAND TRANSPORT (US DOT)

DOT Proper Shipping Name

QTPO123:
UN1866, Resin Solution, 3, PGII, LTD. QTY.

GTPO123:
UN1866, Resin Solution, 3, PGII

DOT Hazard Class:

3

DOT Hazard Label:

FLAMMABLE LIQUID

UN/NA Number:

1866

Packing Group:

II

LAND TRANSPORT (Canadian TDG)

MATERIAL SAFETY DATA SHEET

Bulldog Adhesion Promoter

Page: 8
 Printed: 07/24/2009
 Revision: 07/23/2009
 Supersedes Revision: 10/09/2008

UN Number: 1866
Packing Group: II

Additional Transport Information

For D.O.T. information, contact W.M. Barr Technical Services at 1-800-398-3892.

15. Regulatory Information

US EPA SARA Title III

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. Toluene {Benzene, Methyl-; Toluol}	108-88-3	No	Yes 1000 LB	Yes	Yes
2. Styrene {Phenylethylene; Vinyl benzine; Styrol}	100-42-5	No	Yes 1000 LB	Yes	Yes
3. m-Xylene {Benzene, m-Dimethyl-}	108-38-3	No	Yes 1000 LB	Yes	No
4. o-Xylene {Benzene, o-Dimethyl-}	95-47-6	No	Yes 1000 LB	Yes	No
5. p-Xylene {Benzene, p-Dimethyl-}	106-42-3	No	Yes 100 LB	Yes	Yes
6. Ethylbenzene {Ethylbenzol; Phenylethane}	100-41-4	No	Yes 1000 LB	Yes	Yes
7. Divinyl benzene (Benzene, Diethenyl-)	1321-74-0	No	No	No	
8. Methyl ethyl ketone {MEK; 2-Butanone}	78-93-3	No	Yes 5000 LB	No	Yes
9. Butyl acetate {Acetic acid, Butyl ester}	123-86-4	No	Yes 5000 LB	No	No
10. Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	111-76-2	No	No	Yes-Cat. N230	
11. Ethyl methacrylate	97-63-2	No	Yes 1000 LB	No	

US EPA CAA, CWA, TSCA

Hazardous Components (Chemical Name)	CAS #	EPA CAA	EPA CWA NPDES	EPA TSCA	CA PROP 65
1. Toluene {Benzene, Methyl-; Toluol}	108-88-3	HAP	Yes	Inventory, 8A CAIR	Yes
2. Styrene {Phenylethylene; Vinyl benzine; Styrol}	100-42-5	HAP	Yes	Inventory, 8A CAIR	
3. m-Xylene {Benzene, m-Dimethyl-}	108-38-3	HAP		Inventory	
4. o-Xylene {Benzene, o-Dimethyl-}	95-47-6	HAP		Inventory	
5. p-Xylene {Benzene, p-Dimethyl-}	106-42-3	HAP		Inventory, 4 Test, 8A PAIR	
6. Ethylbenzene {Ethylbenzol; Phenylethane}	100-41-4	HAP	Yes	Inventory	Yes
7. Divinyl benzene (Benzene, Diethenyl-)	1321-74-0	No		Inventory	
8. Methyl ethyl ketone {MEK; 2-Butanone}	78-93-3	No		Inventory	
9. Butyl acetate {Acetic acid, Butyl ester}	123-86-4	No	Yes	Inventory	
10. Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	111-76-2	No		Inventory	
11. Ethyl methacrylate	97-63-2	No		Inventory	

SARA (Superfund Amendments and Reauthorization Act of 1986) Lists:

- Sec.302:** EPA SARA Title III Section 302 Extremely Hazardous Chemical with TPQ. * indicates 10000 LB TPQ if not volatile.
- Sec.304:** EPA SARA Title III Section 304: CERCLA Reportable + Sec.302 with Reportable Quantity. ** indicates statutory RQ.
- Sec.313:** EPA SARA Title III Section 313 Toxic Release Inventory. Note: -Cat indicates a member of a chemical category.
- Sec.110:** EPA SARA 110 Superfund Site Priority Contaminant List

TSCA (Toxic Substances Control Act) Lists:

- Inventory:** Chemical Listed in the TSCA Inventory.
- 5A(2):** Chemical Subject to Significant New Rules (SNURS)
- 6A:** Commercial Chemical Control Rules
- 8A:** Toxic Substances Subject To Information Rules on Production

MATERIAL SAFETY DATA SHEET

Bulldog Adhesion Promoter

Page: 9

Printed: 07/24/2009

Revision: 07/23/2009

Supersedes Revision: 10/09/2008

8A CAIR:	Comprehensive Assessment Information Rules - (CAIR)
8A PAIR:	Preliminary Assessment Information Rules - (PAIR)
8C:	Records of Allegations of Significant Adverse Reactions
8D:	Health and Safety Data Reporting Rules
8D TERM:	Health and Safety Data Reporting Rule Terminations
12(b):	Notice of Export

Other Important Lists:

CWA NPDES:	EPA Clean Water Act NPDES Permit Chemical
CAA HAP:	EPA Clean Air Act Hazardous Air Pollutant
CAA ODC:	EPA Clean Air Act Ozone Depleting Chemical (1=CFC, 2=HCFC)
CA PROP 65:	California Proposition 65

International Regulatory Lists:

EPA Hazard Categories:

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

- Yes No Acute (immediate) Health Hazard
- Yes No Chronic (delayed) Health Hazard
- Yes No Fire Hazard
- Yes No Sudden Release of Pressure Hazard
- Yes No Reactive Hazard

Regulatory Information

This product has been classified according to the hazard criteria of the Controlled Products Regulations.

Concentrations reported in section 2 are weight/weight

Ingredient disclosed in section 2 are on Canadian DSL

16. Other Information

Company Policy or Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.